

SUPERHAUL 30

Specifications

Model AET8130-10S

Marketing Name	SUPERhaul 30
GVWR (lbs)	10,000#
GAWR (lbs/axle)	5200#
Curb Weight (Base)	2450#
Payload	7450#
Frame Construction	6" Tube
Frame Wall Thickness	3/16"-1/4"
Tounge Length (Deck to Ball)	56"
Tongue	6" Tube A-Frame
Coupler	2-5/16"
Jack	5000# Top wind
Fenders	1/8" smooth aluminum, removable
Suspension	Torsion Axle (Galv)
Axle spacing	S Models (42" spread)
Brakes	12" Electric self Adjust
Tires	225/75R15 Load Range D
Wheels	15", 6 on 5.5
Decking	Aluminum
Lighting	LED
Electrical	7-Way RV-Style Molded Plug
Overall length	426"
Bed Length	360
Bed Width	81"
Beaver Tail	N/A
Width Between Wheel Wells	83"
Distance from trailer front to front of wheel wells	167"
Distance from back of trailer to back of wheel wells	115"
Deck Height	24"
Coupler Height	20"
Ramp	6.5' straight ramps
Extended Ramp Length	80"
Optional Front Rock Guard Height	50"

Standard

- Tongue Tool box
- Front Rail
- Stake pockets (fits 2X4)
- Rub rail
- Straight Ramps
- Safety chains
- Towing organizer for 7 way plug and safety chains
- Backup Lights
- Stainless Steel Hardware

Options

- Spare Tire
- Winch (winch, mount, battery tray, electrical)
- Reverse winch kit (D-Ring and Pulley)
- Rock Guard (48" and 36")
- Side Ramps (1 set)
- Loading Guides
- Full width Bifold ramp w/ Spring Assist